


Circular air distribution system


UK-PP – circular pipe



- UK-PP-100/350, UK-PP-100/1000, UK-PP-125/350, UK-PP-125/1000, UK-PP-150/1000
- PVC material
- operating temperature -15 °C to +60 °C

Type	D1 [mm]	D2 [mm]	L [mm]	weight [kg]
UK-PP-100/350	100	103	350	0.233
UK-PP-100/1000	100	103	1000	0.664
UK-PP-125/350	125	128	350	0.355
UK-PP-125/1000	125	128	1000	1.015
UK-PP-150/1000	150	154	1000	1.330


UK-OSP – arches 45°



- UK-OSP-100/45, UK-OSP-125/45
- material tough polystyrene (white)
- operating temperature -15 °C to +60 °C

Type	D1 [mm]	D2 [mm]	A [mm]	s [mm]	weight [kg]
UK-OSP-100/45	99	96	126	26	0.060
UK-OSP-125/45	124	121	150	30	0.102


UK-OSP – arches 90°



- UK-OSP-100/90, UK-OSP-125/90, UK-OSP-150/90
- material tough polystyrene (white)
- operating temperature -15 °C to +60 °C

Type	D1 [mm]	D2 [mm]	A [mm]	s [mm]	weight [kg]
UK-OSP-100/90	99	96	126	26	0.070
UK-OSP-125/90	124	121	150	30	0.140
UK-OSP-150/90	149	146	184	30	0.190

UK-OBJ – T junctions




- UK-OBJ-100/100, UK-OBJ-125/125, UK-OBJ-150/150
- material tough polystyrene (white)
- operating temperature -15 °C to +60 °C

Type	D1 [mm]	D2 [mm]	L [mm]	s [mm]	weight [kg]
UK-OBJ-100/100	99	96	168	26	0.120
UK-OBJ-125/125	124	121	197	30	0.174
UK-OBJ-150/150	149	146	222	30	0.220

Circular air distribution system


UK-SP – couplings



- UK-SP-100, UK-SP-125, UK-SP-150
- material tough polystyrene (white)
- operating temperature -15 °C to + 60 °C

Type	D1 [mm]	D2 [mm]	L [mm]	s [mm]	weight [kg]
UK-SP-100	99	96	58	26	0.038
UK-SP-125	124	121	62	30	0.052
UK-SP-150	149	146	62	30	0.070


UK-SPK – clutches with non-return valve



- UK-SPK-100, UK-SPK-125, UK-SPK-150
- material tough polystyrene (white)
- operating temperature -15 °C to + 60 °C

Type	D1 [mm]	D2 [mm]	L [mm]	s [mm]	weight [kg]
UK-SPK-100	99	96	58	26	0.045
UK-SPK-125	124	121	62	30	0.070
UK-SPK-150	149	146	62	30	0.100

UK-PRO – transitions



- UK-PRO-125/100, UK-PRO-150/125
- material tough polystyrene (white)
- operating temperature -15 °C to + 60 °C

Type	D1 [mm]	D2 [mm]	D3 [mm]	L [mm]	weight [kg]
UK-PRO-125/100	99	96	129	60	0.040
UK-PRO-150/125	124	121	153	60	0.042