



OBJL 45° – einseitiger Abzweig, OBJLG 45° – einseitiger Abzweig mit Dichtung




- die Montage erfolgt durch Pressen
- Lüftung, Klima
- Anschluss an das Rohr mit selbstschneidenden Schrauben

Ø d3 [mm]	Ø d1 [mm]																									
	80		100		125		150		160		180		200		224		250		280		300		315			
	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2
80	185	165	185	180	185	195	185	215	185	225	185	240	185	250	-	-	-	-	-	-	-	-	-	-	-	-
100	-	-	210	200	210	220	215	235	215	245	215	260	215	270	215	290	215	305	-	-	-	-	-	-	-	-
125	-	-	-	-	250	245	250	260	250	270	250	285	250	295	250	315	250	330	250	355	250	365	-	-	-	-
140	-	-	-	-	-	-	270	275	270	285	270	300	270	310	270	330	270	345	270	370	270	380	270	395	270	405
150	-	-	-	-	-	-	285	285	285	295	285	310	285	320	285	340	285	355	285	380	285	390	285	405	285	415
160	-	-	-	-	-	-	-	-	300	305	300	320	300	330	300	350	300	365	300	390	300	400	300	415	300	435
180	-	-	-	-	-	-	-	-	-	-	325	340	325	350	325	370	325	385	325	410	325	420	325	435	325	455
200	-	-	-	-	-	-	-	-	-	-	-	-	355	370	355	390	355	405	355	430	355	440	355	455	355	480
224	-	-	-	-	-	-	-	-	-	-	-	-	-	-	390	415	390	435	390	455	390	465	390	480	390	505
250	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	440	455	440	480	440	490	440	505	440	530
280	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	480	510	-	-	480	515	480	545
300	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	510	545	-	-	-	-
315	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	530	570	-	-

OBDL 90° – einseitiger Abzweig, OBDLG 90° – einseitiger Abzweig mit Dichtung



Ød	ØD:	100	125	140	160
80		•	•	-	-
100		•	•	•	-
125		-	•	•	-
140		-	-	•	•
160		-	-	-	•



Ød	ØD:	200	225	250	315
80		-	-	-	-
100		•	-	-	•
125		•	•	•	•
140		•	•	•	•
160		•	•	•	•
180		•	•	•	•
200		•	•	•	•
225		-	•	•	•
250		-	-	•	•
280		-	-	-	•
315		-	-	-	•

- die Montage erfolgt durch Pressen
- Lüftung, Klima
- Anschluss an das Rohr mit selbstschneidenden Schrauben