





PAR – electrically operated blind flap



- plastic frame and flaps
- color gray RAL7035
- control servo motor 230V/50Hz, closed without voltage (using springs), permanently open under voltage
- the maximum speed for air supply is 3 m/s
- the maximum speed for air removal is 10 m/s
- newly also size 1000, dimensions on request
- on request PAR-E (economic version), opening time approx. 3 min.

| Model | Ø a | b | c | d | Ø e | fan |
|---------|-----|-----|-----|----|-----|-----|
| PAR-160 | 160 | 194 | 140 | 22 | 5 | 150 |
| PAR-200 | 210 | 244 | 182 | 21 | 5 | 200 |
| PAR-250 | 260 | 294 | 232 | 26 | 5 | 250 |
| PAR-315 | 314 | 346 | 276 | 26 | 5 | 315 |
| PAR-355 | 360 | 397 | 310 | 26 | 5 | 355 |
| PAR-400 | 420 | 462 | 366 | 26 | 5 | 400 |
| PAR-450 | 460 | 501 | 395 | 31 | 5 | 450 |
| PAR-500 | 510 | 548 | 443 | 31 | 5 | 500 |
| PAR-560 | 560 | 605 | 522 | 31 | 5 | 560 |
| PAR-630 | 630 | 696 | 626 | 31 | 5 | 630 |
| PAR-710 | 710 | 760 | 692 | 40 | 5 | 710 |
| PAR-800 | 800 | 840 | 772 | 40 | 5 | 800 |

PRG – rain blind



sizes 900 and 1000 on request

- plastic frame and slats
- color gray RAL7035
- the slats are solid
- maximum ambient temperature +70°C
- maximum speed of 12 m/s

| Model | Ø a | b | c | d | Ø e | f | fan |
|---------|-----|-----|-----|----|-----|----|-----|
| PRG-160 | 152 | 178 | 130 | 20 | 4 | 30 | 150 |
| PRG-200 | 210 | 245 | 190 | 20 | 5 | 30 | 200 |
| PRG-250 | 260 | 299 | 235 | 25 | 5 | 45 | 250 |
| PRG-315 | 310 | 347 | 274 | 26 | 5 | 44 | 315 |
| PRG-355 | 360 | 397 | 310 | 26 | 5 | 44 | 355 |
| PRG-400 | 423 | 460 | 364 | 26 | 5 | 39 | 400 |
| PRG-450 | 460 | 501 | 395 | 31 | 5 | 39 | 450 |
| PRG-500 | 510 | 549 | 445 | 31 | 5 | 64 | 500 |
| PRG-560 | 575 | 610 | 530 | 30 | 5 | 50 | 560 |
| PRG-630 | 660 | 701 | 626 | 31 | 5 | 54 | 630 |
| PRG-710 | 710 | 749 | 663 | 31 | 5 | 59 | 710 |
| PRG-800 | – | 830 | 760 | 40 | 5 | 50 | 800 |