




OBJL 45° – odbočka jednostranná, OBJLG 45° – odbočka jednostranná s těsněním



- tvarovka je vyrobena lisováním
- větrání, klimatizace
- spojení s potrubím samořeznými šrouby

Ø d3 [mm]	Ø d1 [mm]															
	80		100		125		150		160		180		200		224	
	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2	L	L2
80	185	165	185	180	185	195	185	215	185	225	185	240	185	250	–	–
100	–	–	210	200	210	220	215	235	215	245	215	260	215	270	215	290
125	–	–	–	–	250	245	250	260	250	270	250	285	250	295	250	315
140	–	–	–	–	–	–	270	275	270	285	270	300	270	310	270	330
150	–	–	–	–	–	–	285	285	285	295	285	310	285	320	285	340
160	–	–	–	–	–	–	–	–	300	305	300	320	300	330	300	350
180	–	–	–	–	–	–	–	–	–	–	325	340	325	350	325	370
200	–	–	–	–	–	–	–	–	–	–	–	–	355	370	355	390
224	–	–	–	–	–	–	–	–	–	–	–	–	–	–	390	415
250	–	–	–	–	–	–	–	–	–	–	–	–	–	–	440	455
280	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–
300	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–
315	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–

OBDL 90° – odbočka oboustranná, OBDLG 90° – odbočka oboustranná s těsněním



- tvarovka je vyrobena lisováním
- větrání, klimatizace
- spojení s potrubím samořeznými šrouby

Ød	ØD:	100	125	140	160
80		•	•	–	–
100		•	•	•	–
125		–	•	•	–
140		–	–	•	•
160		–	–	–	•
Ød	ØD:	200	225	250	315
80		–	–	–	–
100		•	–	–	•
125		•	•	•	•
140		•	•	•	•
160		•	•	•	•
180		•	•	•	•
200		•	•	•	•
225		–	•	•	•
250		–	–	•	•
280		–	–	–	•
315		–	–	–	•